

**myDatalogC33x WIFI/2G/3G/4G World**



**Specifications**

Universal inputs	3 x analogue or digital <ul style="list-style-type: none"> <li>• 0...20mA / 4...20mA</li> <li>• 0...2V / 0...10V</li> <li>• PWM / frequency</li> <li>• Digital/counter</li> </ul>
Serial interface	1 x RS485 (2-wire) 1 x CAN / CAN FD 1 x RS232 (4-wire)
Outputs	2 x isolated switch contact <sup>1)</sup>
Voltage supply	V <sub>in</sub> : 9...32VDC
Operating temp.	-20...+60°C
Integr. buffer battery	Li-Po with 500mAh
Antenna connectors	2 x SMA-F (mobile / WIFI)
Protection class	IP20
USB interface	1 x USB device <sup>2)</sup>
Data memory	512 MB FLASH (3 MB for data) 8 MB RAM, 128kB FRAM
Dimensions (WHD)	70 x 92 x 63mm
Weight	190g
Data transmission	2G/3G/4G World: 2G GPRS 900MHz / 1800MHz 2G GPRS 850MHz / 1900MHz UMTS B1, B2, B5, B8 LTE FDD B1, B2, B3, B4, B5, B7, B8, B12, B13, B18, B19, B20, B26, B28 LTE TDD B38, B39, B40, B41 Wi-Fi (Single-band 2,4 GHz) : <sup>3)</sup> IEEE 802.11 b/g/n Network interface: 10/100 Ethernet
SIM	Integrated SIM chip
Display	RGB-LED (freely usable)
Operation	Button (freely usable)

<sup>1)</sup> parallel connection of PhotoMOS relay and mechanical relay

<sup>2)</sup> only for debugging, script development and production

<sup>3)</sup> useable for communication with sensors usable if not used as uplink

**Application**

The myDatalogC33x WIFI/2G/3G/4G World is a compact, freely programmable device for recording, processing and transmitting signals. It is the perfect multi-functional tool for measurement and control tasks in telecontrol engineering and combines IoT-SPS, router, firewall and data transmission in one device. The universal inputs can be used to record data from analogue sensors and signal transmitters. The RS232, RS485 and CAN interface enables communication with machines, control units or sensors with digital interfaces. 2 isolated switch contacts are available for the control of actuators. The device also has an integrated rechargeable buffer battery that enables a message to be issued in the event of a supply voltage failure.

For bidirectional data exchange with the server either a mobile, WIFI or LAN connection can be chosen. As long as the WIFI interface is not being used as uplink, it is available for interconnecting with devices and sensors.

The core element of the device is the intelligent rapidM2M M23x WIFI/2G/3G/4G World which is especially optimised for high computing power. The device is fitted with the rapidM2M operating system ex-works and is fully functional. The application program can be created within a few hours with the help of the rapidM2M Studio .

**Product characteristics**

- Programmable using rapidM2M Studio
- High processing power (Cortex M4 CPU with FPU)
- Applicable world wide and future-proof thanks to 2G/3G/4G uplink technology
- Universal inputs for digital and analogue signals
- RS232, RS485 and CAN interface
- WIFI interface for communication with sensors
- Isolated switch contact outputs
- Integrated rechargeable buffer battery with charge controller
- Measurement value storage on the device
- Data transmission to the server via mobile network, WIFI or LAN
- Configuration of the device via web portal
- Very low commissioning and operating costs
- Hardware real-time clock
- Integrated durable SIM chip

Scope of supply	Order no.
rapidM2M C3xx Base	301331
rapidM2M M23x WIFI/2G/3G/4G World <sup>4)</sup>	

<sup>4)</sup> inserted in the rapidM2M C3xx Base during production.

One of the following antennae is essential for operation:

- Dome antenna multi band SMA-M 3m(301212)
- Combi Antenna Cellular/Wifi SMA-M 3m(300924)