

myDatasensH2S1000 LTE-M



Technical data

H ₂ S measurement	0-200ppm; max. 1000ppm
range	0,25ppm resolution
	1% repeat accuracy
Temperature	-20+50°C
measurement range	
Operating	-20+50°C
temperature	
Storage and transport	-20+50°C
temperature	
Air humidity	1590%rH non-condensing
Pressure range	Atmospheric +/-10%
Life cycle of the H ₂ S	2 years in the air
sensor	
Protection class	Complete system: IP66
	Gateway: IP66 / IP68 / IP69
	Sensor: IP66
Power supply	Battery
Data memory	82.776 measurement cycles
Dimensions (WHD)	106 x 169 x 61mm
Weight	760g
Transmission	Bluetooth Low Energy (BLE):
	Range of approx.20m
	LTE-M/NB-IoT modem (World):
	M1: LTE B1, B2, B3, B4, B5, B8,
	B12, B13, B14, B18, B19, B20,
	B25, B26, B28, B66
	NB1/NB2: LTE B1, B2, B3, B4, B5, B8, B12, B13, B17, B19,
	B20, B25, B26, B28, B66
Displays	1,5" OLED Display
Displays	1,5 OLED Display

Application

The myDatasensH2S1000 LTE-M is a compact, portable device designed to be operated in wastewater systems to record and transfer H2S concentrations. The innovative sensor replacement considerably reduces the amount of work for maintenance personnel while also ensuring that data is recorded continuously. By using the mobile network to transfer measurement data to the server, the site only has to be physically accessed within the calibration interval (every 6 months) and the data can be accessed at all times.

Fields of application:

- Sewage systems
- Industrial plants
- Municipal water and sewage systems

Product characteristics

- Innovative sensor replacement
- Ecodesign
- Data transmission via BLE or LTE-M/NB-IoT
- · Adjustable record interval
- Colour display of the current measurement values
- Battery operating times of up to 10 years thanks to Ultra Low Power technology
- Compact dimensions
- Robust housing with excellent chemical resistance and rubber casing
- Very low commissioning and operating costs



Scope of supply	Order no.
myDatasensH2S1000 LTE-M	
H2S 7H Sensor module	1
Flat antenna Disc Multi Band FME-F 2m	301259
BLE Gateway MDN Protection casing	301239
USB BLE-Adapter	1
MDN Magnet	

Instead of purchasing the H2S 7H Sensor module it is also available as a "Sensor as a Service" (300706) ¹⁾.

1) Services included: Provision of sensor, reconditioning and replacement of the sensor, calibration, repairs, insurance